



Product certificate K-0215464-1

Issued 2024-04-01

Replaces -

Page 1 of 3

Thermostatic mixing valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Ideal Standard International NV

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline **BRL-K610** "Thermostatic mixers".

which covers the requirements of

EN 1111:2017 "Sanitary tapware; Thermostatic mixing valves (PN10)".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Ideal Standard International NV
Corporate Village – Gent Building
Da Vincilaan 2
B-1935 Zaventem
Belgium
<https://www.idealstandard.de>



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Thermostatic mixing valves

Ceraplust Safe OX

A7606## Serviceless thermostat mixer

For the products mentioned above “##” stands for the colour codes that can be used.

Colours are as follows:

A2	Brushed gold
AA	Chrome
GN	Silver Storm
Q9	Matt champagne / chrome
RO	Rose
Si	Silver
U4	Matt black / chrome
U8	Matt grey pearl / chrome
XG	Silk black
XJ	Stainless steel look

Thermostatic mixing valves

Remark

The above listed products were not yet assessed for compliance with all Hygienic Aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply"), implemented on 01 July 2017, as specified in clause 4.2.2.1 of the Kiwa Evaluation guideline BRL-K610.

Application and use

Thermostatic mixing valves are intended for application in tap water installations with a static water pressure of maximum 1000 kPa and a maximum water temperature of 90°C.

The recommended limits for correct operation are; a working pressure of 100 kPa up to 500 kPa and a water temperature of maximum 65°C.

Marking

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark: on the body.

Compulsory specifications:

- name or mark of the manufacturer: on the body;
- indication for temperature selection: on the control device;
- the acoustic group, if classified: on the body;
- the flow rate class: on the body.

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Ideal Standard Produktions-GmbH
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.