

Product certificate **K-0215796-1**



Issued

2024-05-01

Replaces

Page

1 of 3

Single taps and mixer taps

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Duravit AG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K652 "Sanitary tapware; single taps and mixer taps" dated 10-10-2018,

which covers the requirements of

NEN-EN200:2008: "Sanitary tapware – Single taps and combination taps for water supply systems of type 1 and type 2 – General technical specification.

Ron Scheepers

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00 Fax +31 88 998 44 20

NL.Kiwa.info@Kiwa.com

www.kiwa.nl

Company

Duravit AG

Werderstraße 36

78132 Hornberg

Germany

www.duravit.com



Certification process consists of initial and regular assessment of:

- quality system
- product

page 2 of 3

Single taps and mixer taps

PRODUCT SPECIFICATION

The products mentioned below belong to this product certificate;

Series Manhattan

MH10800020xx Pillar tap

Series No.1

N110800020xx Pillar tap

Series Waveline

WA10600050xx 3-hole basin mixer

WA10800020xx Pillar tap

The colour code (xx) of the Manhattan and Waveline series single taps can be as follows:

- 10 Chrome
- 46 Black matt
- 04 Brushed bronze
- 34 Polished gold
- 70 Brushed Stainless Steel

The colour code (xx) of the No.1 series single taps can be as follows:

- 10 Chrome
- 46 Black matt

APPLICATION AND USE

Sanitary tapware, shower heads and hand showers are designed for application within the following limits of use:

- Working pressure from 50 kPa up to 1000 kPa;
- Water temperature of maximum 90°C.

The recommended limits for correct operation are:

- Working pressure from 50 kPa up to 1000 kPa;
- Water temperature of maximum 65°C.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA".

Place of the mark: on the body

Compulsory specifications:

- Name or mark of manufacturer, on the body;
- · Indication for temperature selection, on the handle;
- The acoustic group, if classified, on the body;
- The flow rate class, on the body.

Method of marking:

- Non-erasable;
- · visible after assembly.

page 3 of 3

Single taps and mixer taps

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- · the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

Duravit AG

and, if necessary,

Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.