



## Product certificate K109903/01

Issued 2022-12-01

Replaces -

Page 1 of 3

### Close coupled suites

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### Grohe AG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K621 "Close coupled suites" dated 02-10-2019

which covers the requirements of

EN 997:2012 + A1: 2015 "WC pans with integral trap".

Ron Scheepers  
Kiwa

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

#### Kiwa Nederland B.V.

Sir Winston Churchilllaan 273  
Postbus 70  
2280 AB RIJSWIJK  
The Netherlands  
Tel. +31 88 998 44 00  
Fax +31 88 998 44 20  
[NL.Kiwa.info@Kiwa.com](mailto:NL.Kiwa.info@Kiwa.com)  
[www.kiwa.nl](http://www.kiwa.nl)

#### Company

Grohe AG  
Industriepark Edelburg  
58675 HEMER  
Germany  
Tel. +49 2372930  
[info@grohe.com](mailto:info@grohe.com)  
[www.grohe.com](http://www.grohe.com)



Certification process  
consists of initial and  
regular assessment of:

- quality system
- product

Close coupled suites

---

**Technical specification**

The products mentioned below belong to this certificate.  
Unless otherwise mentioned the products specified are classified as Class 1 products.  
The products are in compliance with the requirements of EN997:2012 + A1:2015

---

**Close coupled suites BauEdge**

Configured with outlet valve WDI Xiamen B4910T  
Nominal flush volume 5 and 6 litres

Model BauEdge  
WC-pan no. 39811000, concealed horizontal outlet;  
Flushing cistern no. 39861000 with R&T Xiamen bottom inlet valve  
A1370; nominal flush volume 5 litres

Model BauEdge  
WC-pan no. 39811000, concealed horizontal outlet;  
Flushing cistern no. 39812000 with R&T Xiamen side inlet valve  
A1423; nominal flush volume 5 litres

## Close coupled suites

---

### Application and use

Close coupled suites are designed as flushing devices to be connected to drinking water installations with a maximum water temperature of 30 °C.

### Marking

The WC pan, cistern and float operated valve of the close coupled suites are marked with the word mark "KIWA".  
On the WC-pan this word mark shall be followed by the number 6, indicating the flushing volume.

Example:

*Close coupled suite marked as follows:*

*WC-pan: "KIWA-6"*

*Cistern: "KIWA"*

*Float valve: "KIWA"*

*By this marking it is given that the close coupled suite is Kiwa certified and intended for use with a full flush of 6 litres. This flushing volume is indicated by the highest waterline in the cistern.*

Place of the mark:

- on the WC-pans between the attachment holes of the lavatory seat or on the sides;
- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level.

Compulsory specifications:

name or mark of the manufacturer:

- on the WC-pans between the attachment holes of the lavatory seat or on the sides;
- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level;
- additional marking or labelling as specified in the European Standard EN997.

Method of marking:

- indelible;
- visible after assembly.

### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Grohe AG
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.