



## Product certificate K11344/08

Issued 2024-02-01

Replaces K11344/07

Page 1 of 2

### Reinforced plasticized polyvinylchloride (PVC-P) membranes

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### Sika Deutschland GmbH

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K519 "Plasticized polyvinylchloride (PVC-P) membranes, with or without reinforcement" dated June 21, 2019.

Ron Scheepers  
Kiwa

*Publication of the certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

#### Kiwa Nederland B.V.

Sir Winston Churchillaan 273  
Postbus 70  
2280 AB RIJSWIJK  
Tel. 088 998 44 00  
Fax 088 998 44 20  
[info@kiwa.nl](mailto:info@kiwa.nl)  
[www.kiwa.nl](http://www.kiwa.nl)

#### Company

Sika Deutschland GmbH  
Mülheimer Straße 26  
53840 TROISDORF  
Germany  
Tel. +49(0)2241 / 14500  
[info@sika-trocal.com](mailto:info@sika-trocal.com)  
[www.sika.com](http://www.sika.com)

Certification process  
consists of initial and  
regular assessment of:

- quality system
- product

## Reinforced plasticized polyvinylchloride (PVC-P) membranes

### PRODUCT SPECIFICATION

#### General

Reinforced plasticized polyvinylchloride (PVC-P) membranes, in accordance with evaluation guideline BRL-K519 "Plasticized polyvinylchloride (PVC-P) membranes, with or without reinforcement".

#### Further specification

The types and thicknesses, as indicated in undermentioned table, belong to this certificate.

The membrane can be delivered with a nominal width of maximum 2,05 m

Product name – Type	Color	Type	Effective membrane thickness in mm (crossed)				
			0,5	0,8	1,0	1,3	1,5
Sikaplan WP 5120	Black	MB	X	X	X		X
	Grey	MB			X		
Sikaplan WP 5170	Grey	MB + UV	X	X	X		X

#### Application and use

The products are intended to be used in the following situations;

- Roads and hydraulic applications
- Protection of the environment (not for permanent contact with hazardous media)
- Foil type MB also for storage of (animal) manure;
- Foil type UV also for non-covered applications.

Refer in all cases to paragraph 1.2 "area of application" of BRL-K519 for the possible applications per foil type and thickness.

#### MARKING

The products are marked with the Kiwa-mark.

Marking method: with indelible ink.

Position of the mark: on the membrane at least once every 2 m, and on the packing per roll.

Compulsory specifications:

- word mark Kiwa;
- trade name or registered trademark;
- production code;
- PVC-P;
- type of membrane;
- batch number;
- thickness.

#### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Sika Deutschland GmbH
- and, if necessary,
- Kiwa Nederland B.V.

For the correct method of storage, transport and handling, please refer to the processing instructions of the certificate holder.