



Product certificate K13366/08

Issued 2024-08-01

Replaces K13366/07

Page 1 of 3

Shower hoses for sanitary tapware

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Hansgrohe SE

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline

BRL-K668: "Shower hoses for sanitary tapware", dated 01-12-2018.

which covers the requirements of

EN 1113: 2015 "Shower hoses for sanitary tapware for water supply systems of type 1 and type 2 – General technical specification".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.com

Company
Hansgrohe SE
Austraße 59
D-77761 Schiltach
Germany
Tel. +49 78 36 51 0
Fax +49 78 36 51 300
E-mail info@hansgrohe.com
www.hansgrohe.com



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Shower hoses for sanitary tapware

PRODUCT SPECIFICATION

The products mentioned below belong to this certificate;

Type	Article number	Length
SAN- AS	30 61 4910	2.00 m
Isiflex-B	28 278 xx0	0.80 m
	28 272 xx0	1.25 m
	28 282 xx0	1.25 m
	28 622 xx0	1.25 m
	28 277 xx0	1.50 m
	28 712 xx2	1.50 m
	28 276 xx0	1.60 m
	28 286 xx0	1.60 m
	28 626 xx0	1.60 m
	28 275 xx0	1.75 m
	28 713 xx2	1.75 m
	28 274 xx0	2.00 m
	28 714 xx2	2.00 m
	28 284 xx0	2.00 m
	28 624 xx0	2.00 m
Metaflex-C	28 152 xx0	1.25 m
	28 644 xx0	1.25 m
	28 161 xx0	1.25 m
	28 262 xx0	1.25 m
	28 153 xx0	1.50 m
	28 645 452	1.50 m
	28 263 xx0	1.50 m
	28 645 002	1.50 m
	28 264 xx0	1.50 m
	28 266 xx0	1.60 m
	28 166 xx0	1.60 m
	28 155 xx0	1.75 m
	28 265 xx0	1.75 m
	28 646 xx0	1.75 m
	28 154 xx0	2.00 m
	28 647 002	2.00 m
	28 647 452	2.00 m
	28 164 xx0	2.00 m
	28 264 xx0	2.00 m
Axor	28 112 xx0	1.25 m
	28 116 xx0	1.60 m
	28 120 xx0	2.00 m
AXOR ShowerSolutions	28 227 xx0	1.25 m
	28 228 xx0	1.25 m
	28 259 xx0	1.60 m
	28 261 xx0	1.60 m
	28 290 xx0	2.00 m
	28 291 xx0	2.00 m
Comfortflex	28 167 xx0	1.25 m
	28 168 xx0	1.60 m
	28 162 xx0	1.75 m
	28 169 xx0	2.00 m
Designflex	28 220 xx0	1.25 m
	28 230 xx0	2.00 m
	28 260 xx0	1.60 m
Sensoflex	28 132 xx0	1.25 m
	30 400 718	1.25 m
	28 175 xx2	1.50 m
	28 734 xx2	1.50 m
	30 401 918	1.50 m
	28 136 xx0	1.60 m
	30 400 818	1.60 m
	28 735 xx2	1.75 m
	30 402 018	1.75 m
	28 134 xx0	2.00 m
	28 736 xx2	2.00 m
	30 400 918	2.00 m

Shower hoses for sanitary tapware

REMARK

The specified products were not yet assessed for compliance with all aspects as inserted in the Dutch Drinking Water Decree and outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation materials and chemicals drinking water and warm tap water supply"), implemented 19 July 2011. As specified in the mentioned regulations, a transition period applies. As soon as the final policy has been defined the products shall be tested in accordance with Clause 4.3.1 of Kiwa evaluation guideline BRL-K668/03.

APPLICATION AND USE

Shower hoses for sanitary taps according to EN 1113 are intended for application in drinking water installations with a dynamic pressure of 50 kPa to 500 kPa and a maximum water temperature of 70°C. The recommended limits for correct operation are a dynamic pressure of 100 kPa to 300 kPa and a maximum water temperature of 42°C.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA".
Place of the mark: on the shower hose.

Compulsory specifications:

- name or mark of the manufacturer.

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Hansgrohe SE
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.