





K20141/06 Replaces

1 of 3 Page



Stop and connecting cocks

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Válvulas Arco S.L.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-604 "Stop and connecting cocks" dated 2022-01-07.

Ron Scheepers

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273 P.O. Box 70 2280 AB RIJSWIJK The Netherlands

Fax +31 88 998 44 20

info@kiwa.nl

www.kiwa.nl

Tel. +31 88 998 44 00

Company

Válvulas Arco S.L. Avda, del Cid. 8 46134 FOIOS-VALENCIA Spain

Tel. +34 96 149 9429 Fax +34 96 149 9428 tecnica@valvulasarco.es www.valvulasarco.es



Certification process consists of initial and regular assessment of:

- quality system
- product

Stop and connecting cocks

PRODUCT SPECIFICATION

The products mentioned below belong to this product certificate.

The designs mentioned in this certificate are made of brass, unless otherwise mentioned.

Angled connecting cocks in the following types

1. WI743

A-80 Standard 10 mm x G1/2A

Standard& long nut; chromed / plastic handle

2. K0702

A-80 Standard 10 mm x G1/2A

Standard nut; chromed / plastic handle

3. K0742

A-80 Standard 10 mm x G1/2A

Long nut; chromed / plastic handle

4. K0713

A-80 short 10 mm x G1/2A

Long nut; polished chromed / plastic handle

5. WI727

A-80 short 10 mm x G1/2A

Standard & long nut; chromed / plastic handle

6. K0790

A-80 short 10 mm x G1/2A

Standard nut; chromed / plastic handle

7. K0727

A-80 short 10 mm x G1/2A

Long nut; chromed / plastic handle

8. SC791

A-80 short G1/2A x G3/8A

Plastic handle with SCHWAB logo;

chromed/ brass; delivered with applied thread patch

9. KZ702

A-80 standard 10 mm x G1/2A

Standard nut; chromed / Zamak handle

10. K0791

A-80 short G1/2A x G3/8A

Plastic handle with ARCO logo; chromed/ brass; delivered with applied thread patch

11. K0792

A-80 short G1/2A x G3/8A

Plastic handle with ARCO logo; chromed/ brass; delivered with PTFE-ring

12. K0793

A-80 short G1/2A x G3/8A

Zamak handle with ARCO logo; chromed/ brass; delivered with PTFE-ring

13. KZ742

A-80 standard 10 mm x G1/2A

Long nut; chromed / Zamak handle

14. KZ727

A-80 short 10 mm x G1/2A

Long nut; chromed / Zamak handle

15. 2402TK

MINI filter G1/2A x G3/8A

Chromed handle

With compression fittings type no. 1690380 or no. 1690360

16. 201210

G% x G1/2

Plastic nut

Plastic screw-in handle

17. NF721SI

G 1/2 x G3/8

Plastic screw-in handle

18. 00711

G ½ x G ½

Screw-in handle

19. 201240

G 1/2 x G3/8

For cistern, without handle

page 3 of 3

Stop and connecting cocks

FITNESS FOR CONTACT WITH DRINKING WATER

The listed products are approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The products shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- · Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'Appendix Hygienic Aspects' to this certificate.

APPLICATION AND USE

Stop- and connecting cocks are designed to be used in tap water installations with a maximum working pressure of 1000 kPa and a water temperature with a maximum of 65 °C. Using the products in water installations with a water temperature up to 90 °C is possible. However, this may influence the durability of some parts and the contact temperature of the operation handle.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA" together with the Watermark logo Place of the mark: on the body.

Compulsory specifications:

On the body:

- Flow direction (applicable to stop- and connection cocks with drainage connections);
- Nominal diameter;
- · Company name, trademark, or logo.

On the head part (if applicable):

· Company trademark.

On the union of the compression joint (if applicable):

- Company trademark;
- Nominal diameter.

Method of marking:

- indelible;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Válvulas Arco S.L.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.