



Product certificate K42694/08

Issued 2024-07-01

Replaces K42694/07

Page 1 of 3

PPSU fittings

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Fränkische Rohrwerke Gebr. Kirchner GmbH Co

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline **BRL-K536 K** "Multilayer piping systems PE-X/Al, PE-RT/Al, PP-R/Al and PP-RCT/Al intended for transport of hot and cold drinking water inside buildings" dated 15-11-2017.

Ron Scheepers
Kiwa

*This product certificate is only valid in combination with a Kiwa certified plastics piping system.
Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.*

CERTIFICATE

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Fränkische Rohrwerke Gebr.
Kirchner GmbH Co
Hellinger Straße 1
97486 KÖNIGSBERG/BAYERN
Germany
Tel. +49 9525 88 2411
info@fraenkische.de
www.fraenkische.com



Certification process
consists of initial and
regular assessment of:

- quality system
- product

PPSU fittings

TECHNICAL SPECIFICATION

The product complies to BRL K536-K multilayer piping systems PE-X/Al, PE-RT/Al, PP-R/Al and PP-RCT/Al intended for transport of hot and cold drinking water inside buildings.

Subject

PPSU Fittings

Product characteristics

The product complies to BRL-K536 K "Multilayer piping systems PE-X/Al, PE-RT/Al, PP-R/Al and PP-RCT/Al intended for transport of hot and cold drinking water inside buildings.

Specification

The fittings are suitable for the pipe dimensions stated in the table below

Nominal diameter (mm)	Press system	Push-Fit system
16	X	X
20	X	X
26	X	X
32	X	-
40	X	-
50	X	-
63	X	-

Colour of the fittings: white

Remarks:

- PPSU mechanical press fittings with dimensions 16, 20, 26 and 32 mm with press contour F, TH and U.
- Dimensions 40, 50 and 63 mm only with press contour F

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government

Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.





The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The products shall be marked with the Kiwa-mark.

Fittings

The minimum required marking on the fittings shall be:

- **KIWA**  or on small products  or  or **KK** or **KK** (if not possible **KIWA**  only on the smallest packaging unit);
- Kiwa (if not possible Kiwa only on the smallest packaging);
- the manufacturer's name, trade name or logo;
- nominal outside diameter of the corresponding pipe;
- production code.

The realization of the marks is as follows: clear, durable and indelible.

The smallest packaging unit of the fittings are provided with at least the following information:

- **KIWA**  ;

PPSU fittings

- certificate number of the accompanying technical approval-with-product certificate of the piping system, according the marking of the belonging pipe;
- the manufacturer's name, trade name, system name or logo;
- material identification if the fitting body is made of plastics;
- nominal outside diameter and nominal wall thickness of the corresponding pipe in mm.

The realization of the marks is as follows: clear, durable and indelible.

Logistics

Production and assembly of the system is laid down in the annex of the certification agreement.

APPLICATION AND USE

The products are designed for drinking water installations with a lifetime of 50 years at an operating temperature profile according to class 2 of ISO 10508 and an allowable working pressure of maximum 10 bar.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Fränkische Rohrwerke Gebr. Kirchner GmbH Co
and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.