



Product certificate K44708/03

Issued 2017-11-01

Replaces K44708/02

Page 1 of 2

Thermostatic mixing valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Carlo Nobili S.p.A. Rubinetterie

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K610/04: "Thermostatic mixing valves" dated 01-02-2012, which covers the requirements of

EN 1111: 1998: "Sanitary tapware; Thermostatic mixing valves (PN10)".

Luc Leroy
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

P. O. Box 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00

Fax +31 88 998 44 20

info@kiwa.nl

www.kiwa.nl

Company

Carlo Nobili S.p.A. Rubinetterie

Via Lagone 32

28021 BORGOMANERO

Italy

Tel. +39 0322 844555

Fax +39 0322 846489

info@nobili-spa.com

www.nobili-spa.com

Certification process
consists of initial and
regular assessment of:

- quality system
- product

Thermostatic mixing valves

PRODUCT SPECIFICATION

The products mentioned below belong to this product certificate;

Article no. 30700 Build-in model, without flow control

REMARK

The above listed products were not yet assessed for compliance with all Hygienic Aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply), implemented on 19 July 2011, as specified in clause 4.2.2.1 of the Kiwa Evaluation guideline BRL-K610/04.

APPLICATION AND USE

Thermostatic mixing valves are intended for application in tap water installations with a static water pressure of maximum 1000 kPa and a maximum water temperature of 90°C.

MARKING

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark: on the body.

Compulsory specifications:

- name or mark of the manufacturer: on the body;
- indication for temperature selection: on the control device;
- the acoustic group, if classified: on the body;
- the flow rate class: on the body.

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Carlo Nobili S.p.A. Rubinetterie

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.