

Product certificate **K6187/07**



Issued

2021-08-15

Replaces

K6187/06

Page

1 of 3

Connecting valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Grohe AG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K604 "Stop- en aansluitkranen" dated 01-12-2018.

Ron Scheepers

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00 Fax +31 88 998 44 20

NL.Kiwa.info@Kiwa.com

www.kiwa.nl

Company

Grohe AG

Industriepark Edelburg

58675 HEMER

Germany

Tel. (+49) 2372 930

Fax (+49) 2372 931322

info@grohe.com

www.grohe.com





Certification process consists of initial and regular assessment of:

- quality system
- product

Product certificate

page 2 of 3

Connecting valves

PRODUCT SPECIFICATION

The products mentioned below belong to this technical approval-with-product certificate

22018000	G1/2" x G3/8"	standard handle, metal escutch.
2201800M	G1/2" x G3/8"	standard handle, metal escutch.
22019000	G1/2" x G3/8"	standard handle
22023000	G1/2" x G3/8"	standard handle, metal escutch., self-sealing
2202300M	G1/2" x G3/8"	standard handle, metal escutch., self-sealing
22024000	G1/2" x G3/8"	standard handle, self-sealing
2202500M	G1/2" x G1/2"	standard handle, metal escutch.
22026000 22026000	G1/2" x G1/2"	standard handle
2202700M	G1/2" x G1/2"	standard handle, metal escutch., self-sealing
22028000	G1/2" x G1/2"	standard handle, metal escutori, self-sealing
22029000	G1/2" x G3/8"	standard handle, metal escutch.
22029000	G1/2" x G3/8"	standard handle, metal escutch, self-sealing
22031000	G1/2" x G1/2"	standard handle, metal escutch.
22032000	G1/2" x G3/8"	
22037000	G1/2" x G3/8"	metal handle, metal escutch. metal handle
22039000	G1/2" x G3/8"	metal handle, metal escutch., self-sealing
22040000	G1/2" x G3/8"	metal handle, self-sealing
22041000	G1/2" x G1/2"	metal handle, metal escutch.
22042000	G1/2" x G1/2"	metal handle
22043000	G1/2" x G1/2"	metal handle, metal escutch., self-sealing
22044000	G1/2" x G1/2"	metal handle, self-sealing
22045000	G1/2" x G3/8"	metal handle, metal escutch.
2204700M	G1/2" x G3/8", cap	standard handle, metal escutch.
22046000	G1/2" x G1/2"	metal handle, metal escutch.
2204800M	G1/2" x G3/8", cap	standard handle, metal escutch., self-sealing
22049000	G1/2" x G3/8", cap	metal handle, metal escutch.
22051000	G1/2" x G3/8", cap	metal handle, metal escutch., self-sealing
22052000	G3/8" x G3/8"	standard handle, metal escutch., self-sealing
22053000	G3/8" x G3/8"	standard handle, metal escutch.
490405045	G3/8" x R1/2"	PA water connection valve.

page 3 of 3

Connecting valves

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA **, or KK in a rectangle KK

Place of the mark:

on the body

Compulsory specifications:

- · Manufacturers name Grohe, on the body;
- Nominal size: "DN", on the body and compression fitting (if applicable).

Method of marking:

- Non-erasable;
- visible after assembly.

APPLICATION AND USE

Connecting valves are intended to be used in drinking water installations with a maximum operating pressure of 1000 kPa and a water temperature of maximum 90°C. The recommended limits for correct use are a maximum operating pressure of 500 kPa and a water temperature of maximum 65°C.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- · the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

Grohe AG

and, if necessary,

• Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.