

# Technical-approval-with-product certificate **K93147/04**



Issued

2023-07-15

Replaces

K93147/03

Page

1 of 3

# **SYSTEMPEX**

#### STATEMENT BY KIWA

With this technical-approval-with-product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

# Van Marcke NV

as specified in this technical-approval-with-product certificate and marked with the Kiwa<sup>®</sup>-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline **BRL-K536 E** "Plastics piping systems of PE-X/Al intended for transport of hot and cold drinking water" dated 15-12-2011 inclusive amendment sheet dated 13-03-2018.

Within the framework of this technical-approval-with-product certificate Kiwa does not impose any inspections with regard to the production of other parts of the (product), nor the manufacturing of the (product) itself.

Ron Scheepers

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

#### Kiwa Nederland B.V.

Sir Winston Churchilllaan 273 Posthus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00

Fax +31 88 998 44 20

NL.Kiwa.info@Kiwa.com

www.kiwa.nl

### Company

Van Marcke NV

Lar Blok 25

B-8511 AALBEKE

België

Tel. +32 56 237 511



Certification process consists of initial and regular assessment of:

- quality system
- product

page 2 of 3

# Plastics piping systems of PE-X/AI intended for transport of hot and cold drinking water

#### **TECHNICAL SPECIFICATION**

#### Subject

SYSTEMPEX

#### **Product characteristics**

The product complies to BRL K536-E Plastics piping systems of PE-X/Al intended for transport of hot and cold drinking water.

The system consists of:

- Plastic pipes of PE-Xb/Al/PE-Xb;
- Metal press fittings.

#### Specification

The dimensions of the pipe in the table below are part of this certificate.

Nominal outside diameter (mm)	Wall thickness (mm)	Wall thickness aluminum layer (mm)	Pressing profile fittings
16	2,0	0,20 / 0,30	TH
20	2,0	0,25 / 0,40	TH
26	3,0	0,35 / 0,58	TH
32	3,0	0,40 / 0,75	TH
40	3,5	0,80	TH
50	4,0	1,00	TH
63	4,5	1,20	TH

Colour: Inner pipe Natural

White Outer pipe

Colour of the fitting: Brass Body

> Press sleeve Stainless steel

#### Fitness for contact with drinking water

The pipes and fittings used in this system are approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" dated 01-07-2017; ("Materials and chemicals in the supply of drinking water and warm tap water Regulation"; published in the Government Gazette). The criteria for these hygienic aspects are recorded in the respective product certificates.

#### **MARKING**

The products shall be marked with the Kiwa-mark.

The minimum required marking on the pipes shall be:

- **KIWA** or \* + class 2/ 10 bar; material identification: PE-Xb;
- the build up of the pipe: PE-Xb/Al/PE-Xb;
- certificate number of accompanying technical approval-with-product certificate of the piping system;
- the manufacturer's name, trade name, system name or logo;
- nominal outside diameter in mm;
- nominal wall thickness of the pipe in mm;
- production code.

The realization of the marks is as follows: clearly, durable and indelible at intervals of not more than 2 meters.

<sup>\*)</sup> for smaller diameters permitted by Kiwa.

page 3 of 3

# Plastics piping systems of PE-X/AI intended for transport of hot and cold drinking water

#### **Fittings**

The minimum required marking on the fittings shall be:

- KIWA or on small products or KK or KK (if not possible KIWA on the smallest packaging unit);
  - the manufacturer's name, trade name or logo;
- nominal outside diameter of the corresponding pipe;
- production code.

The realization of the marks is as follows: clearly, durable and indelible.

The smallest packaging unit of the fittings are provided with at least the following information:

# KIWA 👹

- certificate number of the accompanying technical approval-with-product certificate of the piping system, according the marking of the belonging pipe;
- the manufacturer's name, trade name, system name or logo;
- material identification if the fitting body is made of plastics;
- nominal outside diameter and nominal wall thickness of the corresponding pipe in mm.

The realization of the marks is as follows: clearly, durable and indelible.

#### **Protection pipes**

The minimum required marking on the protection pipes shall be:

- Kiwa (or Kiwa<sup>®</sup> word mark);
- the manufacturer's name, trade name, certificate number of the protection pipe or the certificate number of the belonging technical approval (system) certificate.

The realization of the marks is as follows: clearly and indelible at intervals of not more than 2,5 m.

#### **LOGISTICS**

Production and assembly of the system is laid down in the annex of the certification agreement.

#### **APPLICATION AND USE**

The medium pipes and fittings are designed for drinking water installations with a lifetime of 50 years at an operating temperature profile according to class 2 of NEN-ISO 10508 and an allowable working pressure of maximum 10 bar.

The corrugated protection pipes have to protect the medium pipes in case the medium pipes are embedded.

#### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- · the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

Van Marcke NV

and, if necessary,

Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage, transport and processing methods.