



KOMO® Product certificate K10431/07



Issued	2022-03-15	Replaces	K10431/06
Valid until	Indefinite	Dated	2020-09-01
Page	1 of 2		

3-layer PVC pipes for soil and waste discharge inside buildings

Dyka B.V.

STATEMENT BY KIWA

This product certificate is based on Guideline/BRL 2023 "Pipes and fittings with structured smooth wall for soil and waste discharge inside buildings – Type A: PVC-U, PP" dated 9 January 2017, issued according to the Kiwa-Regulation for Certification.

The quality system and the product characteristics of this product are checked periodically. Based on this, **Kiwa declares that** there is legitimate confidence that:

Upon delivery, the product supplied by the certificate holder meets the requirements:

- Of the technical specifications laid down in this product certificate,
- The product requirements as laid down in the Guideline.

Provided the product is accompanied by the KOMO® quality mark in the manner set out in this product certificate.

Ron Scheepers
Kiwa

*This product certificate is also included on the KOMO foundation websites: www.komo.nl and www.komo-online.nl.
Users of this product certificate is advised to check whether it is still valid. For this purpose consult the website of Kiwa: www.kiwa.nl.*

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Certificate holder
Dyka B.V.
Produktieweg 7
8331 LJ STEENWIJK
Postbus 33
8330 AA STEENWIJK
Tel. +31 (0)521-534911
Fax +31 (0)521-534371
info@dyka.nl
www.dyka.nl

Production location
Dyka SAS
Rue de Brévillers 25
62140 SAINTE-AUSTREBERTHE
France
Tel. +33 (0)321 86 59 00
Fax +33 (0)321 86 59 01



Assessed is:
• Quality system
• Product
Periodic control

3-layer PVC pipes for soil and waste discharge inside buildings

PRODUCT SPECIFICATION

3-layer pipes of PVC-U for soil and waste discharge inside buildings in accordance with BRL 2023.

The products in the table below are part of this product certificate.

The pipes can be provided with integrated sockets.

Colour: red-brown and grey

Table 1

Outside diameter (mm)	Dyka B.V.		Dyka SAS	
OD	SN8	SN4	SN8	SN4
40		X		X
50		X		X
75		X		X
90		X		X
110	X	X	X	X
125	X	X	X	X
160	X	X	X	X


MARKING

The products shall be marked with the KOMO®-mark.

The realization of the marks is as follows: clear, durable and indelible.

Location of the marks: on every pipe at intervals of not more than 2 m.

The pipes shall be marked with at least the following marks:

- KOMO word mark or logo ;
- certificate number;
- manufacturer's name or trade name;
- material designation;
- classification, for Ø 110 mm up to and including Ø 200 mm;
- nominal outside diameter in mm;
- production period or production code.

Marking with BRL 2023 is optional.

APPLICATION AND USE

The products are intended to be used in a plastic piping system for non-pressure underground drainage and sewerage.

Take into account the following installation guidelines:

- the processing guidelines of the producer.

PROCESSING GUIDELINES

The supplier shall provide processing instructions.

The instructions drawn up in the Dutch language shall contain specific information with regard to storage, transport and installation of the products.

TIPS FOR THE USER

Check on delivery of the products listed under the "technical specification" whether:

- The product(s) and material(s) ordered are delivered in accordance with the agreement you made.
- The brand and the method of marking is correct
- No defects or damage is visible (for example, resulting from the transportation).

If on the basis of the foregoing you decide to proceed to rejection, please contact

- Dyka B.V.

And if necessary,

- Kiwa Nederland B.V.

Verify if this product certificate is still valid, see the website of Kiwa Netherlands.

