



Product certificate K10790/05

Issued 2022-02-01

Replaces K10790/04

Page 1 of 3

Flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Grohe AG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K620 "Flushing cisterns" dated 15-09-2019.

Which covers the requirements of

EN14055: 2010 + A1: 2015 "WC and urinal flushing cisterns" June 2015.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company
Grohe AG
Industriepark Edelburg
58675 HEMER
Germany
Tel. +49 2372930
info@grohe.com
www.grohe.com



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Flushing cisterns

Technical specification

Rapid SL

Prod. No.	Description	Height	Cistern no.	Remarks
38340000	Rapid SL	1,20 m	67448	same as 38528, with other frame
38525000	Rapid SL	1,00 m	66415	
38526000	Rapid SL	0,82 m	66490	
38528000	Rapid SL	1,20 m	67448	
38536000	Rapid SL	1,20 m	67448	same as 38528, with fastening material for WC
38539000	Rapid SL	1,20 m	67448	same as 38528, with fastening material for WC + noise reduction
38584000	Rapid SL + heavy foot	1,20 m	67448	same as 38528, with other frame
38587000	Rapid SL + heavy foot	0,82 m	66490	same as 38526, with other frame
38678000	Rapid SL DIY	1,20 m	67448	same as 38528, with fastening mat. for WC, other packaging

Rapid SLX

39596000	Rapid SLX	1,13 m	492.623	
39597000	Rapid SLX	1,13 m	492.623	same as 39596000, without outlet waste pipe
39598000	Rapid SLX	1,13 m	492.623	same as 39596000 with wall brackets and noise protection

Unisets

38415000	Uniset AV1, SpK	0,82 m	66492	
38643000	Uniset, WC SpK 6-9 I	1,20 m	67447	
38646000	Uniset, WC SpK 6-9 I	1,20 m	67447	
38705000	Uniset, WC SpK 6-9 I	1,20 m	67447	

On wall mounted cisterns

38422000	stortbak voor WC	0,82 m	66490	without frame
38661000	stortbak voor WC	1,20 m	67448	without frame

Above mentioned cisterns are equipped with the following float valves

06.30.9400	for cistern SK GD2	1,20 m	6-9 I.
67055040	for cistern SK 0,82	0,82 m	6-9 I.

Above mentioned cisterns are equipped with the following outlet valves

66110040	for cistern SK GD2	1,20 m	6-9 I.
66416040	for cistern SK 0,82	0,82 m	6-9 I.

Flushing cisterns

Application and use

Flushing cisterns (in combination with WC pans) are intended for use

as flushing units connected to drinking water installations with a water temperature of maximum 30 °C.

Flushing cisterns using a flush volume of 6 ± 0.2 litres are intended for use in connection with WC-pans of the type 6A, according to guideline BRL-K 619

Marking

The products are marked with the Kiwa-mark.

Method of marking:

- indelible
- visible after mounting.

Compulsory specifications:

Manufacturers mark or logo

- the float valve: -on the body
- the cistern: -on the left- right- under- or front side or on the inside above the maximum water level.

Place of the marks:

- the float valve : -on the body
- the cistern: -on the left- right- under- or front side or on the inside above the maximum water level.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Grohe AG
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.