



Product certificate K23075/07

Issued 2023-03-15

Replaces K23075/06

Page 1 of 3

CERTIFICATE

Flushing Cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

TECE GmbH

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K620 "Flushing Cisterns" dated 15-09-2019.

Which covers the requirements of

EN14055: 2010 + A1: 2015 "WC and urinal flushing cisterns" June 2015.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

P.O. BOX 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00

Fax +31 88 998 44 20

info@kiwa.nl

www.kiwa.nl

Company

TECE GmbH

Hollefeldstraße 57

48282 EMSDETTEN

Germany

Tel. +49 02572 / 9280

info@dece.de

www.dece.de

Certification process
consists of initial and
regular assessment of:

- quality system
- product

Flushing Cisterns

Technical specification

The products mentioned below belong to this certificate.

Unless otherwise mentioned the products mentioned in this certificate can be configured with:

- a float operated valve (inlet valve) Sanit, type Univ 510 or TECE type F10 (with brass threaded connection).
- flexible hose type DN8 as specified in Kiwa certificate K84779 or K84782.
- angled connecting cock as specified in Kiwa certificate K21115 or K6097.

Concealed flushing cisterns using a nominal flush volume of 6 litres

Flushing cistern TECE UNI, installation height 1120mm - Model SP100 094 01

With side connection, provided with flush pipe and equipped with:

- Flushing device TECE, flush mechanism type A2-2019 type SP209 006 10

In various designs with the following product numbers:

- No. 9.240.2xx – Manual dual flush panel (xx=color variations)
- No. 9.240.3xx – Infra-red flush panel (xx = 12V and color variations)

Flushing cistern TECE UNI, installation height 980mm - Model SP100 095 00

With side connection, provided with flush pipe and equipped with:

- Flushing device TECE, flush mechanism type A2-2019 type SP209 006 10

In various designs with the following product numbers:

- No. 9.240.2xx – Manual dual flush panel (xx=color variations)

Flushing cistern TECE UNI, installation height 820mm - Model SP100 093 00

With side connection, provided with flush pipe and equipped with:

- Flushing device TECE, flush mechanism type A2-2019 type SP209 006 11

In various designs with the following product numbers:

- No. 9.240.2xx – Manual dual flush panel (xxx=color variations)

Flushing cistern TECE Octa II, 8cm - Model SP120 011 00

With side connection, provided with flush pipe and equipped with:

- Flushing device TECE, flush mechanism type A5 type SP209 013 00

In various designs with the following product numbers:

- No. 9.240.2xx – Manual dual flush panel (xxx=color variations)

Flushing cistern TECEprofil toilet module integrated hygiene flush

Model SP100 083 00, with side connection, provided with flush pipe (elbow) and equipped with:

- Flushing device TECE, Ablaufventil A2-2019 type SP209 006 10 with interrupting flush
- Connecting valve Fluhs BF000028171 / SP219 019 00
- Flexible hose Luxor DN8

Note

This product is related to the safety certificate K109925. The issued certificates for the certification scheme for aspects of technical water supply protection for appliances with a contamination risk are not covered by accreditation.

Flushing Cisterns

APPLICATION AND USE

The flushing cisterns are intended to operate in combination with WC-pans as hygienical flushing devices to be connected to drinking water installations with a water temperature of maximum 30°C. Flushing cisterns with an affective flushing volume of 6 litres are designed for connection to WC-pans of the type 6A (see also Kiwa BRL-K619).

MARKING

The Kiwa®-mark products are marked with the wordmark "KIWA"

Place of the mark:

- on the cisterns on the left side, right side or front or on the inside above water level;
- on the body of the float operated valve (filling valve).

Compulsory specifications:

name or mark of the manufacturer

- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level.

Method of marking:

- indelible;
- visible after assembly (for concealed flushing cisterns after demounting of the control panel).

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- TECE GmbH

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.