



Product certificate K6248/10

Issued 2023-08-15

Replaces K6248/09

Page 1 of 3

Flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Geberit International AG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K620 "Flushing cisterns" dated 15-09-2019.

Which covers the requirements of

EN14055: 2010 + A1: 2015 "WC and urinal flushing cisterns" June 2015.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company
Geberit International AG
Schachenstrasse 77
CH-8645 JONA
Switzerland
Tel. +41 (0) 55 221 63 00
info@geberit.com
www.geberit.com

Supplier
Geberit B.V.
Fultonbaan 15
3439 NE NIEUWEGEIN
The Netherlands
Tel. +31 30 605 7700
info.nl@geberit.com
www.geberit.nl



**Certification process
consists of initial and
regular assessment of:**

- quality system
- product

Flushing cisterns

Technical specification

The following types are included in this certificate.

Concealed flushing cisterns

In the following type(s):

Model Sigma concealed flushing cistern 12 cm (UP320)

Flushing cistern with front operation; nominal flush volume of 6 and 7 litres; equipped with Dual Flush system Typ212; Float operated valve type Impuls 380; delivered with flush pipe (elbow);

Operation plate(s):

- Samba - Twist
- Rumba - Tango
- Mambo – Sigma

Built-in frames Kombifix, Duofix, Gis and Sanbloc

Model Delta concealed flushing cistern 12 cm (UP100)

Flushing cistern with front operation; nominal flush volume 6 and 7 litres; equipped with Dual Flush system Typ212; float operated valve type Impuls 380; delivered with flush pipe (elbow);

Operation plate(s):

- Delta

Built-in frames Kombifix, Duofix, Gis and Sanbloc

Model Sigma concealed flushing cistern 8 cm (UP720)

Flushing cistern with front operation; nominal flush volume 6 and 9 litres; equipped with Dual Flush system; float operated valve type Impuls 380; delivered with flush pipe (elbow);

Operation plate(s):

- Samba - Twist
- Rumba - Tango
- Mambo - Sigma

Built-in frames Kombifix, Duofix, Gis and Sanbloc

Model Omega concealed flushing cistern 12 cm

Flushing cistern with front or top operation; nominal flush volume 6 and 7 litres; equipped with Dual Flush system Typ212; float operated valve type Impuls 380; delivered with flush pipe (elbow);

Operation plate(s):

- Omega

Built-in frames Kombifix, Duofix, Gis and Sanbloc

High level flushing cistern(s)

In the following type(s):

Model AP123 High level flushing cistern

Flushing cistern with cover; nominal flush volume 6, 7 and 9 litres; Float operated valve type Impuls 380; with G3/8 side inlet connection at left side, right side or middle rear; delivered with nut for 32 mm flush pipe.

Low level flushing cisterns

In the following type(s):

Model AP140 Low level flushing cistern

Flushing cistern with a nominal flush volume of 6 and 9 litres; equipped with a Dual Flush system; Float operated valve type Impuls 380; with G3/8 side inlet connection at left side, right side or middle rear; delivered with flush pipe (elbow);

- no. 140.314. series (with cover lock)

- no. 140.317. series

Model AP123 Low level flushing cistern

Flushing cistern with a nominal flush volume of 6 and 9 litres; equipped with a Flush Stop system; Float operated valve type Impuls 380; with G3/8 side inlet connection at left side, right side or middle rear; delivered with flush pipe (elbow).

Model AP120 Low level flushing cistern

Flushing cistern with a nominal flush volume of 6 and 9 litres; equipped with a Flush Stop system type AP120; Float operated valve type 333; with G3/8 side inlet connection at left side or right side connection; delivered with flush pipe (elbow).

Flushing cisterns

Application and use

The products are intended to be applied as a flushing device for WC-pans. The flushing cisterns in combination with a matching WC-pan is designed to be used as a sanitary flushing installation with a nominal flush volume as specified in Table 1 of BRL-K620. The cisterns are designed for drinking water installations with a maximum water temperature of 30 °C and a maximum working pressure of 1000 kPa.

Marking

The products are marked with the Kiwa-mark.

Place of the mark:

- the float valve : on the body
- the cistern: on the left-, right-, bottom-, or front- side, or on the inside above the maximum water level

Compulsory specifications:

- Manufacturers mark or logo:
 - the float valve: on the body;
 - the cistern: on the left-, right-, bottom-, or front-side, or on the inside above the maximum water level;
- Markings and designations according to clause 10 of EN 14055.

Method of marking:

- non-erasable;
- visible after mounting (for concealed and built-in flushing cisterns, after removal of operation panel).

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Geberit International AG
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.