



Product certificate K98374/02

Issued 2019-07-01

Replaces K98374/01

Page 1 of 3

Flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Fluidmaster Inc.

as specified in this product certificate and marked with the Kiwa[®]-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K620/06 "Flushing cisterns" dated 22-09-2014.

Which covers the requirements of

EN14055: 2010 + A1: 2015 "WC and urinal flushing cisterns" June 2015

Ronald Karel
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

289171015

Kiwa Nederland B.V.
Sir Winston Churchilllaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Company
Fluidmaster Inc.
Rancho Viejo Road 30800
CA92675 SAN JUAN
CAPISTRANO
United States of America
Tel. (+1) 949.728.2000
www.fluidmaster.com

Certification process
consists of initial and
regular assessment of:

- quality system
- product

Flushing cisterns

Technical specification

The products mentioned below belong to this certificate

Concealed flushing cisterns using a nominal flush volume of 6 litres, with interrupted flushing device, side inlet connection, including matching flush pipes.

1. Flushing cisterns T02-0100Kiwa with configuration:
 - float valve Fluidmaster, type 747E16B (with brass inlet connection)
 - flushing device type Fluidmaster B01
 - flexible hose, type Parigi
 - angled connecting cock, type AGG103684

In various frame designs with the following product numbers:

 - No. T02-0111
 - No. T02-0112
 - No. T02-0113
 - No. T02-0114
 - No. T02-0115
 - No. T02-0116
 - No. T02-0117
 - No. T02-2113
 - No. T02-2114
 - No. T02-2115
 - No. T02-2116
 - No. T02-3114
 - No. T02-0120
 - No. T02-0130
 - No. T02-0140

Supplied with Fluidmaster flush plates with manual operation.
2. Flushing cisterns T02V1-0100Kiwa with configuration:
 - float valve Fluidmaster, type 747E16B (with brass inlet connection)
 - flushing device type Fluidmaster B01
 - flexible hose, type Parigi
 - angled connecting cock, type Albertoni AGG103684

In various frame designs with the following product numbers:

 - § T02V1-0112-0250 / 670050
 - § T02V1-2113-0250 / 670051
 - § T02V1-0130-0250 / 670052

T02v1 Schwab executions compatible with Schwab MAGNUS 670069/70/71 , HYDRA 670063/64/65 , METIS 670060/61/62, VENTUS 670072/73/74 manual operated flush plates
3. Flushing cisterns T02V2-0100Kiwa with configuration:
 - float valve Fluidmaster, type 747E16B (with brass inlet connection)
 - flushing device type Fluidmaster B01
 - flexible hose, type Parigi
 - angled connecting cock, type Albertoni AGG103684

In various frame designs with the following product numbers:

 - § T02V1-0112-0250 / 670050
 - § T02V1-2113-0250 / 670051
 - § T02V1-0130-0250 / 670052

T02v1 Schwab executions compatible with Schwab MAGNUS 670069/70/71 , HYDRA 670063/64/65 , METIS 670060/61/62, VENTUS 670072/73/74 manual operated flush plates
4. Flushing cisterns T02V1-0100-0250 with configuration:
 - float valve Fluidmaster, type 747EBSCW (with brass inlet connection)
 - flushing device type Fluidmaster B07
 - flexible hose, type Parigi
 - angled connecting cock, type Albertoni AGG103684

In various frame designs with the following product numbers:

 - § T02V1-0112-0250 / 670050
 - § T02V1-2113-0250 / 670051
 - § T02V1-0130-0250 / 670052

T02v1 Schwab executions compatible with Schwab MAGNUS 670069/70/71 , HYDRA 670063/64/65 , METIS 670060/61/62, VENTUS 670072/73/74 manual operated flush plates
5. Flushing cisterns T02V1-0100-0310 with configuration:
 - float valve Fluidmaster, type 747EBSCW (with brass inlet connection)
 - flushing device type Fluidmaster B01
 - flexible hose, type Parigi
 - angled connecting cock, type AGG103684

In various frame designs with the following product numbers:

 - § T02v1-0112-0310 / 8050452510 (WISA execution)
 - § T02v1-0130-0310 / 8050452504 (WISA execution)
 - § T02v1-2113-0310 / 8050452515 (WISA execution)

T02v1 WISA executions compatible with WISA ARGUS 8050414601/31/51/14, MAROS 8050414401/31/51, DELOS 8050415601/31/51/38, flush plates
6. Flushing cisterns T02V2-0100-0250 with configuration:
 - float valve Fluidmaster, type 747EBSCW (with brass inlet connection)
 - flushing device type Fluidmaster B01
 - flexible hose, type Parigi
 - angled connecting cock, type Albertoni AGG103684

In various frame designs with the following product numbers:

 - § T02V1-0112-0250 / 670050
 - § T02V1-2113-0250 / 670051
 - § T02V1-0130-0250 / 670052

T02v1 Schwab executions compatible with Schwab MAGNUS 670069/70/71 , HYDRA 670063/64/65 , METIS 670060/61/62, VENTUS 670072/73/74 manual operated flush plates
7. Flushing cisterns T02V2-0100-0310 with configuration:
 - float valve Fluidmaster, type 747EBSCW (with brass inlet connection)
 - flushing device type Fluidmaster B01
 - flexible hose, type Parigi
 - angled connecting cock, type AGG103684

In various frame designs with the following product numbers:

 - § T02v1-0112-0310 / 8050452510 (WISA execution)
 - § T02v1-0130-0310 / 8050452504 (WISA execution)
 - § T02v1-2113-0310 / 8050452515 (WISA execution)

T02v1 WISA executions compatible with WISA ARGUS 8050414601/31/51/14, MAROS 8050414401/31/51, DELOS 8050415601/31/51/38, flush plates
8. Flushing cisterns T07-0100KIWA with configuration:
 - float valve Fluidmaster, type 747E16B (with brass inlet connection)
 - flushing device type Fluidmaster B07
 - flexible hose, type Parigi
 - angled connecting cock, type Albertoni AGG103684

Compatible with Fluidmaster flush plates manual operated
9. Flushing cisterns T07b-0100KIWA with configuration:
 - float valve Fluidmaster, type 747E16B (with brass inlet connection)
 - flushing device type Fluidmaster B07
 - flexible hose, type Parigi
 - angled connecting cock, type ECI0001

Compatible with Fluidmaster flush plates manual operated

Flushing cisterns

Application and use

Flushing cisterns (in combination with WC pans) are intended for use as flushing units connected to drinking water installations with a water temperature of maximum 30°C. Flushing cisterns are intended for use in connection with WC-pans according to the evaluation guideline BRL-K619.

Marking

Place of the mark:

The Kiwa®-mark products are marked with the word mark "KIWA"

- on the cisterns: on the left side, right side or front or on the inside above water level;
- on the body of the float operated valve (inlet valve).

Compulsory specifications:

name or mark of the manufacturer:

- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level.
- reference to the European Standard EN14055;

Method of marking:

- indelible;
- visible after assembly (for concealed flushing cisterns after demounting of the control panel).

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Fluidmaster Inc.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.