



## Product certificate K43802/10

Issued 2021-05-01

Replaces K43802/09

Page 1 of 7

### Vulcanised rubber products for cold and hot drinking water applications

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

#### **LOPIGOM S.p.a.**

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K17504 "Vulcanised rubber products for cold and hot drinking water applications" dated 10-10-2018.

Ron Scheepers  
Kiwa

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

CERTIFICATE

287180711

**Kiwa Nederland B.V.**  
Sir Winston Churchillaan 273  
Postbus 70  
2280 AB RIJSWIJK  
The Netherlands  
Tel. +31 88 998 44 00  
Fax +31 88 998 44 20  
NL.Kiwa.info@Kiwa.com  
[www.kiwa.nl](http://www.kiwa.nl)

**Company**  
Lopigom S.p.a.  
Via Rossini 11  
24060 Credaro (BG)  
Italy  
Tel: +39 035 92 70 98  
info@lopigom.com  
www.lopigom.com



Certification process  
consists of initial and  
regular assessment of:







- quality system
- product

Vulcanised rubber products for cold and hot drinking water applications












**PRODUCT SPECIFICATION**

The products as specified in the table below fulfil the requirements of BRL-K17504. BRL-K17504 covers the requirements of EN 681-1, "Elastomeric seals - Materials requirements for pipe joint seals used in water and drainage applications - Part 1: Vulcanized rubber".



















**TECHNICAL SPECIFICATION OF THE PRODUCT**

<b>Rubber Compound: EPDM Lopi 50</b>					
Hardness:	50 IRHD	Field of application <sup>2</sup> :	II – WB	Remarks:	
Ozone Class <sup>1</sup> :	I	Production method:	Injection moulding		
	Seal type	<b>O-ring</b>			
	Nominal Dimensions	10 - 160 mm			
	Cross sections	2 - 10 mm			
<b>Rubber Compound: EPDM Lopi 60</b>					
Hardness:	60 IRHD	Field of application <sup>2</sup> :	II – WB	Remarks:	
Ozone Class <sup>1</sup> :	I	Production method:	Injection moulding		
	Seal type	<b>O-ring</b>			
	Nominal Dimensions	10 - 160 mm			
	Cross sections	2 - 10 mm			
<b>Rubber Compound: EPDM Lopi 70</b>					
Hardness:	70 IRHD	Field of application <sup>2</sup> :	II – WB	Remarks:	
Ozone Class <sup>1</sup> :	I	Production method:	Injection moulding		
	Seal type	<b>O-ring</b>		Seal type	<b>Seal with Stainless Steel reinforcement</b>
	Nominal Dimensions	10 - 160 mm		Nominal Dimensions	200 - 800 mm
	Cross sections	2 - 10 mm		Height	5,6 – 7,8 mm
				Width	
<b>Rubber Compound: EPDM Lopi 80</b>					
Hardness:	80 IRHD	Field of application <sup>2</sup> :	II – WB	Remarks:	
Ozone Class <sup>1</sup> :	I	Production method:	Injection moulding		
	Seal type	<b>O-ring</b>		Seal type	<b>Flat seal „Pakkingring EPDM80 ATA“</b>
	Nominal Dimensions	10 - 160 mm		Nominal Dimensions	15 – 52 mm
	Cross sections	2 - 10 mm		Height	2,5 – 4,0 mm
				Width	4,5 – 10 mm
























Vulcanised rubber products for cold and hot drinking water applications

Rubber Compound:	<b>FKM 70 "VI707RF"</b>					
Hardness:	70 IRHD	Field of application <sup>2</sup> :	II – WB	Remarks:		
Ozone Class <sup>1</sup> :	I	Production method:	Injection moulding			
	Seal type	<b>O-ring</b>		Seal type		
	Nominal Dimensions	10 - 160 mm		Nominal Dimensions		
	Cross sections	2 - 10 mm		Height		
				Width		
<b>Technical Seals, membranes and flat rounds produced with EPDM Lopi 50, Lopi 60, Lopi 70 and Lopi 80</b>						
Product codes	Cross Sections [mm]	Nominal Dimensions [mm]	Profiles			
9380-I	3,05	36				
9430-I	2,85 - 6	50,9				
9431-I	3,8 - 8	65,2				
9432-I	3,8 - 8	89,2				
9433-I	4,8 - 10	110,0				
9434-I	5,7 - 12	154				
9435-I	6,7 - 14	175				
9436-I	7,5 - 15	221				
9668-I, 9669-I, 9577-I, 9578-I, 9579-I, 9580-I, 9581-I, 9582-I, 9583-I, 9682-I, 9684-I	2,4 – 4,5	12 - 55				
9659-I, 9660-I, 9661-I, 9662-I, 9663-I, 9664-I, 9713-I	2,3 – 4,5	12 - 51				
9744-I, 9757-I, 9758-I	1,3 – 4,3	11 - 24				
9745-I	2 - 2,5	11				
9769-I	1 – 2,6	10 – 15,7				
9727-I	1,8	3,7				
9705	3,5	6				
9524-P	1,8	12,4				
9512-I	3,5	10,7				
9770-I	1,8	9,3				
9491	3,6	23,4				
9465-I	2,5 – 7,6	7				
9510-I	4 - 11	6				
9539-I	2,5 - 4	20,3				
9564-I	6 – 22,5	8				
9572-I	3	18				
9573-I	2 – 2,5	43				
9574-I	6 - 27	59				
9575-I	5 - 18	6				
9576-I	4 – 8,5	5				
9584-I	4 – 15,3	6				
9597-I	1,7 – 2,7	119,6				
9599-I	1,5 – 4,5	12				
						













Vulcanised rubber products for cold and hot drinking water applications

9600-I	1,4 – 2,8	15,6		
9613-I	2,6 - 2,7	16,2		
9614-I	1,5 - 4	33		
9620-I	3,8 - 4	9,5		
9635-I	3 – 3,5	19		
9681-I	2 – 4,5	10		
9678-I	1,5 – 3,2	8		
9676-LC8	3 – 10,3	8,5		
9675-LC8	3 – 14,5	16		
9674-LC8	2,5 – 5,5	8		
9726-I	2 - 3	30		
9751-I	4,7	9,5		
9755-I	2,6	15		
9756-I	2,7	16,2		
9567-I	1			
9230-I	4	64		
9666-I	4 – 6,5	5		
9460-I	2 - 58	7,1		
9610-P	7,5 - 88	33		
9618-I	3,7- 22	-		
9619-I	3,7 - 15	-		
9617-I	3,7 - 29	-		
9593-I	1,9 - 5	5,1		
9592-I	0,9 - 2			
9601-I	1,2 – 3,2			
9623-I	1,3 – 2			
9624-I	1,3 – 2			
9627-I	1,8 – 2,5			
9596-I	2	6,5 – 36		
9653-I	2,5	19 – 64		
9704-I	2			
9640-I	4			
9734-I	0,5 – 0,6	33 - 75		
9632-P	1,2 – 1,9			
9634-P	1 - 4			
9479-I	3,9			
9409-P	2,5 – 5,5	11		
9594-I	3,4 – 3,5	37,5		
9595-I	2,3 – 3,8	54,8		
9760-I	1,5 – 2,5	3,8		
9743-I	2,7 - 4	5,3		
9437-P	0,6 – 1,8	5,7		
9650-I	2 – 2,5	4,7		

Vulcanised rubber products for cold and hot drinking water applications

9728-I	1,4 - 7	13,6	
9559-P	0,8 – 1,2	13,5	
9615-I	1,5		
9665-I	10		
9695-I	2 – 5,2		
9735-I	1 – 11,5		
9736-I	1 – 5,2		
9742-I	1,4		
9328-I	1 - 5		
9173-I	1 – 3,8	2,4	
9155-I	5 - 7	31,4	
9403-I	0,5 – 2,5		
9404-I	0,4 – 2,6		
9447-P	0,3 – 1,1	18 – 23	
9448-P	0,2 – 1,6	32,6	
9585-I	0,6 – 2,2	23,5	
9649-I	2,5 – 7,6	7	
9708-I	1,5 - 2	16,7	
9731-I	0,7 – 1,5	10,3 - 25	
9732-I		8,2 - 21	
9733-I		12,3 – 36,7	
9472-P	1 - 2	6,5 – 7,5	
9523-P	1,1 – 2,2	3	
9545-I	1,4	118	
9546-I	1	3,5 – 6,2	
9549-I	4,8 - 8	20,2 -16	
9603-I	3,3 – 3,5	10,5	
9609-I	1,5 – 5,5	9,1	
9495-I		12,6	
9611-I		15,5	
9602-I	1,2 – 3,8	9	
9612-I	5,7 – 5,9	7,6	
9633-P	1,1 – 3,5		
9714-I-SOSPESO	4,8 – 7,3	103,5	
9716-I-SOSPESO	5,5 – 8,7	66	

## Vulcanised rubber products for cold and hot drinking water applications

9715-P	5 - 8	78,5	
9723-I	4,8 – 5,4	54	
9729-I	9,1 – 12,7	68,2	
9741-I	3,4 - 5	18	
9598-I	3 – 4,5	7,9	
9568-I	1 - 2	34,7	
9547-I	1 – 3,6	1,4	
9625-I	8 – 15,5	-	
9566-I	1 - 2	6	
9565-I	5 - 11	-	
9478-I	2 – 3,5	9	
9470-I	1,3 -4,5	-	

1 Ozone resistance class according to BRL-K17504:  
 I For products with a high risk of attack by ozone, for instance in case of separately supplied products without sufficient packaging or in case of connections with preinstalled rubbers under strain.  
 II For products for which a normal resistance to ozone is required.  
 III For rubbers which are never (partly) exposed to the open air when they are in tension. Transport shall always take place in sealed packages.

2 Field of application class according to BRL –K17504:  
 I Water supply at temperatures up to 50 °C;  
 II Water supply at temperatures intermittently up to 110 °C, or water supply up to 110 °C in serviceable piping systems;  
 III Hot water circulation systems based on the classification class 2 in ISO 10508;

Field of application class according to EN 681-1:  
 WA As in BRL-K17504 class I;  
 WB As in BRL-K17504 class II;  
 WE As in BRL-K17504 class II, for IIR-copolymer.

Details of the products are included in the drawing list, which forms a part of the IQC schedule.

Kiwa authenticates this list. A copy of this list can be obtained from the producer.

### Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).


These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

### MARKING

The following marks and indications must be provided on each product<sup>#</sup> and product packaging in a clear, legible and indelible way:

- the name of manufacturer or the deposited trade mark;
- Kiwa (or Kiwa® word mark) and additionally the Kiwa watermark ;
- the nominal dimension or dimensions;
- the nominal hardness;
- the year of manufacturing and preferably the quarter;
- type of rubber applied by means of the letter codes of the nomenclature according to ISO 1629;
- the application class (I, II or III);
- on products from blends, the letter B ("blend") shall be placed behind the first letter code;
- the ozone resistance class ("Ozone I, II or III"). For rubber rings made from two compounds the compound with the lowest class is valid.

## Vulcanised rubber products for cold and hot drinking water applications

---

# If the dimensions of the products are such that the indications applied to them may impair the product, the products may be marked per package in consultation with the manufacturer, the buyer and Kiwa. Products produced by cutting or die cutting out of sheets may be marked per package.

### **APPLICATION AND USE**

The rubber rings are meant to be used in cold water applications ( $\leq 25$  °C) and in warm water applications ( $\leq 60$  °C).

### **RECOMMENDATIONS FOR CUSTOMERS**

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- LOPIGOM S.p.a.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.