



Product certificate K6029/08

Issued 2024-04-15

Replaces K6029/07

Page 1 of 3

Flexible connecting hoses

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

UNIWELL Rohrsysteme GmbH & Co. KG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline **BRL-K622** "Flexible connecting hoses", dated 2022-01-07.

which covers the requirements of

EN13618 "Flexible hose assemblies in drinking water installations - Functional requirements and test methods".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

287180711

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

UNIWELL Rohrsysteme GmbH & Co. KG
Siegelfelder Straße 1
D-96106 EBERN
Germany
Tel. +49 9-53192290
info@uniwell.de



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Flexible connecting hoses

PRODUCT SPECIFICATION

The products mentioned below belong to this technical approval-with-product certificate;

KOTT-GLIDE flexible connecting hoses, DN 6 – DN8 – DN13, with the following possible connecting ends::

DN6

union nut 3/8"
 union nut 1/2"
 male thread 3/8"
 male thread 1/2"
 pipe end 8mm
 pipe end 12mm
 pipe end 15mm
 compression fitting 10mm
 compression fitting 12mm
 compression fitting 15mm
 male thread M8x 0,75
 male thread M8x1
 male thread M10x 1
 union nut M15x1
 union nut M9/16" with conical sealing
 nipple for EUP
 nipple for EURO
 nipple for O-Ring
 ball joint nipple
 compression fitting 8mm

DN8

union nut 3/8"
 union nut 1/2"
 union nut 3/4"
 male thread 3/8"
 male thread 3/4"
 male thread 1/2"
 bend 90° ,union nut 3/8"
 bend 90° ,union nut 1/2"
 bend 90° , union nut 3/4"
 pipe end 8mm
 pipe end 10mm
 pipe end 12mm
 pipe end 15mm
 compression fitting 10mm
 compression fitting 12mm
 compression fitting 15mm
 male thread M10x1
 male thread M12 x 1
 male thread M15x1
 union nut M10x1
 union nut M12x1
 union nut M13x1 with conical sealing
 union nut M15x1
 union nut M9/16" with conical sealing
 nipple for EUP
 bend 90° nipple for EUP
 nipple for O-Ring
 ball joint nipple
 pipe end 10 mm 45°angled
 compression fitting 8mm

DN13

union nut 1/2"
 union nut 3/4"
 union nut 1"
 male thread 1/2"
 male thread 3/4"
 bend 90° Union nut 1/2"
 bend 90° union nut 3/4"
 bend 90° union nut 1"
 union nut 1/2", with conical sealing

Flexible connecting hoses

Fitness for contact with drinking water


These products are approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA ", or the abbreviated word mark "KK*
Place of the mark: on the flexible hose (clamp bush).

Compulsory specifications:

- name or mark of manufacturer: on the flexible hose (clamp bush);
- at least the last two digits of the production year: on the flexible hose (clamp bush);
- maximum operating temperature 70 °C: on the flexible hose (clamp bush);
- if supplied with a compression fitting, then, in addition, the manufacturer's mark and nominal size on the coupling nut.

Method of marking:

- Non-erasable;
- visible after assembly.

APPLICATION AND USE

The flexible connecting hoses are intended for application in drinking water installations with a static water pressure of maximum 1000 kPa and a maximum water temperature of 70°C.

Flexible connecting hoses may be used as an integrated part of the appliance.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- UNIWELL Rohrsysteme GmbH & Co. KG

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.