



Product certificate K90662/02

Issued 2023-07-15

Replaces K90662/01

Page 1 of 2

Non controllable backflow preventer with different pressure zones – Family C, type A

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Isiflo B.V.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K648 "Niet controleerbare terugstroombeveiligingstoestellen, met verschillende drukgebieden - familie C, type A" dated 01-12-2018.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Isiflo B.V.
(CENTERPOORT NRD)
Marketing 23
6921 RE DUIVEN
Tel. 026-3195757
info@isiflobv.nl
www.isiflobv.nl



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Non controllable backflow preventer with different pressure zones – Family C, type A

Technical specification

The products mentioned below to this certificate.

Backflow preventer type CA310:

DN15;

DN20.

Remark

The specified products were not yet assessed for compliance with all aspects as inserted in the “Drinkwaterbesluit” and outlined in the “Regeling materialen en chemicaliën drink- en warm tapwatervoorziening” (Regulations Materials and Chemicals for Drinking Water Supplies -implemented 19 July 2011) as specified in the clause 4.2.1 of the Kiwa evaluation guideline BRL-K648/03.

Application and use

The products are intended for use in drinking water installations with a working pressure of maximum 1 MPa (10 bar) and a water temperature of a maximum of 65°C.

Marking

The Kiwa®-mark products are marked with the word mark “KIWA”.

Place of the mark: on the body.

Compulsory specifications:

- Name or mark of the manufacturer;
- Nominal size (DN);
- Arrow indicating the direction of flow;
- Letter indicating family, type and class of the device;
- Nominal pressure (PN);
- Maximum operating temperature (°C);
- Acoustic group, if the backflow preventer is classified;
- Individual identification number;
- Reference to Standard EN 14367.

Method of marking:

- Non erasable;
- Visible after installation.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Isiflo B.V.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier’s processing guidelines for the proper storage and transport methods.