

BRL-K21011/02 GRP tanks for the above ground storage of chemicals



Glass fiber reinforced plastic (FRP) tanks are widely used for the storage of chemicals. The tanks are designed for a maximum pressure of 0.5 bar and temperatures of - 40 to + 120 °C. The BRL-K21011 requirements are based on the requirements of NEN-EN 13121-1 to -4.

For whom?

Installers of storage facilities for chemicals.

When is it necessary?

Companies covered by the Activities Decree (Activiteitenbesluit = BARIM) are legally required to have their chemical storage installation to be installed by an installer certified in accordance with BRL SIKB 7800/BRL-K903. A certified installer must submit an approved RI&E (Risk Inventory & Evaluation) before a certificate in accordance with BRL SIKB 7800/BRL-K903 can be issued. The tanks and spill containers required for the storage of chemicals will be part of this RI&E.

The RI&E of each installation can be streamlined when use is made of certified components. In such cases, the RI&E aspects related to the certified products, are not required. The storage tanks and spill containers, manufactured according to the requirements of BRL-K21011, will be in accordance with the requirements of the BARIM, RARIM and BRL SIKB 7800/BRL-K903.

Interested?

If you are interested in certification, please complete the application form. If you have any questions, please contact our sales office.

Kiwa N.V.
Sir Winston Churchill-laan 273
2288 EA Rijswijk
P.O. Box 70
2280 AB Rijswijk
info@kiwa.nl