

	Type 2		Type 3	
	EN 1111	EN 1287	HP-D08	LP-D08
Max static pressure	10 Bar	10 Bar	10 Bar	10 Bar
Flow pressure, H&C	0.5 to 5 Bar	0.1 to 1 Bar	1 to 5 Bar	0.2 to 1 Bar
Hot Temperature - °C	55 to 65	55 to 65	52 to 65	52 to 65
Cold Temperature - °C	≤ 250	≤ 250	5 to 20	5 to 20

-HP-B	High Pressure	Bidet
-HP-S	High Pressure	Shower
-HP-W	High Pressure	Wash basin
-HP-T44	High Pressure	Bath with fill temp up to 44 <sup>0</sup>
-HP-T46	High Pressure	Bath with fill temp up to 46 <sup>0</sup>
-HP-D44	High Pressure	Bath with fill temp up to 44 <sup>0</sup> and shower up to 41 <sup>0</sup>
-HP-D46	High Pressure	Bath with fill temp up to 46 <sup>0</sup> and shower up to 41 <sup>0</sup>
-LP-B	Low Pressure	Bidet
-LP-S	Low Pressure	Shower
-LP-W	Low Pressure	Wash basin
-LP-D44	Low Pressure	Bath with fill temp up to 44 <sup>0</sup> and shower up to 41 <sup>0</sup>
-LP-D46	Low Pressure	Bath with fill temp up to 46 <sup>0</sup> and shower up to 41 <sup>0</sup>