Assessment program BRL-K916



Certification scheme(s)	BRL-K916/03 "Anti-siphon protection for tank installations" dated 1-4-2018
Scope	Anti-siphon devices
Regulation(s)	Kiwa Regulation for Certification
Frequency of external inspections	The minimum number of visits for BRL-K916/03 is 2 assessments a year and 1 for suppliers with a certified quality-system in accordance with ISO 9001. Remark: An assessment can be an evaluation of the quality system with a test of the functioning of the anti-siphon device and/or a test of the functioning of the anti-siphon device in the Kiwa test rig.

Requirements	Initial	Frequency	Visit 1	Visit 2 Applicable without ISO 9001	Visit 3	Visit 4	Visit 5
Product requirements							
Document review (mandatory at initial inspection)		Gen.	Χ		> <	><	><
Implementation (mandatory at initial inspection)	Х	Gen.	Х		\nearrow	><	><
General product requirements (design)		By changes			\times		\times
Process control		1x/y.	Х				
Product control – testing		e.v.	Х	Х			
Identification		e.v.	Х	Х			
Others (intern transport and storage)		1x/y.	Х		\mathbb{X}	><	><
Requirements to be met by the quality system							
Quality system / Internal quality assurance, quality plan	Х	1x/y.	Х		\mathbb{X}	><	><
Procedures and work instructions	Х	1x/y.	Χ		\times	><	>>
Procedure for customer complaints / Handling of complaints		1x/y.	Χ		\times	><	>
Products with deviations		1x/y.	Χ		> <	><	><
Corrective actions		1x/y.	Х		> <		
Measurement equipment / calibration		1x/y.	Х		> <		
Others							
Use of Kiwa logos and marks	Х	1x/y.	Х		\geq		

Remarks:

- e.v. = every visit.
- Visit 2 could be only a test of the anti-siphon device and check of the identification of it.