

Controllable backflow protection devices, family B, type A (BRL-K646)



The products are intended to be used in drinking water installations with a operating pressure of at most 1MPa (10 bar) and a water temperature at most 65°C.

The functional requirements for these products are based on EN 12729.

Together with necessary peripherals (upstream and downstream valves, sieve, 3 control taps) these products are used as backflow prevention units BA in tap water installations.

For producers, wholesaler installation articles installers.

The Kiwa Water Mark is needed when you, as a producer or supplier, want to profile yourself on the market with products that meet all requirements: all functional requirements as well as all legal hygienic requirements specified in the “Materials and chemicals in the supply of drinking water and warm tap water Regulation” of the Dutch government.

Steps to obtain a certificate with the Kiwa Water Mark are:

1. Fill in an application form and send it to Kiwa (application form is located on the right side);
2. Kiwa sends a quotation, which is at the same time a concept-agreement, drawn up according to the requirements of the guideline;
3. After mutual signing of the quotation, the agreement is definitive and the initial audit can start;
4. After positive results of the initial audit, the certificate will be issued;
5. The certificate is valid indefinitely;
6. A part of the agreement is periodic audits.

Important aspects of the initial audit (steps 3 and 4) include:

a. Testing with regard to the product and/or performance requirements.

Appliances & Installations Nederland

NL.Support.AI@kiwa.com
+31 (0)88 998 45 55



Testing, often carried out in our own laboratories, demonstrates that the product meets the certification requirements for functional and hygienic aspects, such as durability, dimensions, composition of materials, etc.;

b. Assessment of the production process, quality system and internal quality control (IQC) scheme.

To ascertain that the producer is continually able to manufacture products that meet the certification requirements.

The periodic audits aim at the maintenance of the management system, in order to maintain confidence that the producer is still able to manufacture products that meet the certification requirements. The periodic audits include functional and hygienic tests of the certified products. The audit frequency varies from product group to product group: in general, 2 to 4 times per year.

Conditions for the certification process are stated in the Kiwa Regulations for Certification and the General Terms and Conditions of Kiwa for the performance of orders.

**Appliances & Installations
Nederland**

NL.Support.AI@kiwa.com
+31 (0)88 998 45 55

