

Mini hose reel systems for 12mm semi rigid hose (BRL-K14031)



Mini hose reel systems for 12mm semi rigid hose have been designed for fire fighting and other purposes and can be connected to drinking water installations with a maximum water pressure of 1000 kPa and a water temperature of maximum 30°C.

Remark

Mini hose reel products are not as such included in the Dutch Building Regulations. The final decision whether the products may be installed in the framework of the fire safety in public buildings, as alternative to fire hose reels in compliance with the EN 671-1, is up to the competent authorities.

Steps to obtain a certificate are:

1. Fill in an application form and send it to Kiwa (application form is located on the right side);
2. Kiwa sends a quotation, which is at the same time a concept-agreement, drawn up according to the requirements of the guideline;
3. After mutual signing of the quotation, the agreement is definitive and the initial audit can start;
4. After positive results of the initial audit, the certificate will be issued;
5. The certificate is valid indefinitely;
6. A part of the agreement is periodic audits.

Important aspects of the initial audit (steps 3 and 4) include:

- a) Testing with regard to the product and/or performance requirements. Testing, often carried out in our own laboratories, demonstrates that the product meets the certification requirements for functional and hygienic aspects, such as durability, dimensions, composition of materials, etc.;
- b) Assessment of the production process, quality system and internal quality control (IQC) scheme. To ascertain that the producer is continually able to manufacture products that meet the certification requirements.

Appliances & Installations Nederland

NL.Support.AI@kiwa.com
+31 (0)88 998 45 55



The periodic audits aim at the maintenance of the management system, in order to maintain confidence that the producer is still able to manufacture products that meet the certification requirements. The periodic audits include functional and hygienic tests of the certified products.

The audit frequency varies from product group to product group: in general, 2 to 4 times per year.

Conditions for the certification process are stated in the Kiwa Regulations for Certification and the General Terms and Conditions of Kiwa for the performance of orders.

**Appliances & Installations
Nederland**

NL.Support.AI@kiwa.com
+31 (0)88 998 45 55

